

EH type batteries are made in AGM technology and are constructed by plates, separators, safety valves and a container. Since the electrolyte is held by a glass-mat separator and plates, the batteries can be used in any chosen position without the risk of leakage. EH type batteries have a pressure relief valves that allows safe dispersal of any excess pressure inside the cell (VRLA). Due to advantages as sealed construction, maintenance free, low internal resistance and long term storage, EH batteries are the base of the emergency power supplying.




### TECHNICAL DATA

Nominal voltage	12 V	
Nominal capacity	12 Ah / C <sub>20</sub>	
Cell per unit	6	
Technology	AGM	
Design life	5 years @ 20°C*	
	4 years @ 25°C	
Dimensions	height	98,0 mm
	length	151,0 mm
	width	98,0 mm
Weight	~3,35 kg	
	Capacity @ 25°C	
Capacity @ 25°C	20h	0,6A @1,75V/cell 12,0 Ah
	10h	1,14A @1,75V/cell 11,4 Ah
	5h	2,04A @1,75V/cell 10,2 Ah
	1h	7,87A @1,60V/cell 7,87 Ah
Ambient nominal temperature range	charge	0°C ~ 40°C
	discharge	-20°C ~ 50°C
	storage	-20°C ~ 40°C
Internal resistance	@ fully charge battery	≤18,0 mΩ
Charging voltage @ 20°C	standby use	13,5V to 13,8V (-18 mV/°C)
	cycle use	14,4 V to 15,0V (-24 mV/°C)
Charging current	recommended	1,2 A
	maximum	3,6 A
Maximum discharge current (for 5 sec)	180 A	
Capacity retention during storage @ 20°C (self discharge)	after 1 month	97 %
	after 6 months	80 %
	after 12 months	63 %
Container material	standard	ABS UL 94-HB
	optional	ABS UL 94-V0**
Terminal	faston F2	T2
Terminal hardware initial torque	-	


### APPLICATIONS

- uninterruptible power supplies (UPS)
- emergency lighting systems
- telecommunication PABX
- cash registers and fiscal printers
- fire and security systems
- solar powered systems
- medical equipment
- mobile and portable equipment – cycle use
- measuring devices

### DIMENSIONS



### TERMINALS



\*-) - According to Eurobat

\*\*-) - Flame-retardant

### NO TRANSPORT RESTRICTED

Not restricted for air, surface and water transport. Classified as non-hazardous material (IATA/ICAO Special Provision A67, DOT-CFR Title 49 parts 171-189, IMDG amendment 27)

### DISCHARGE CHARACTERISTICS

#### • Constant current (Current [A], 25[°C] / 77[°F])


F.V. V/cell	Discharge time										
	5 min	10min	15min	30min	1h	2h	3h	5h	8h	10h	20h
1,80	39,1	28,1	22,3	12,91	7,34	4,00	2,91	2,01	1,35	1,12	0,59
1,75	46,1	30,5	23,3	13,40	7,56	4,10	2,97	2,04	1,37	1,14	0,60
1,70	48,9	31,6	24,0	13,70	7,70	4,16	3,00	2,05	1,38	1,15	0,60
1,65	51,1	32,3	24,6	13,89	7,79	4,20	3,02	2,06	1,38	1,15	0,61
1,60	52,8	33,0	25,0	14,03	7,87	4,23	3,04	2,06	1,39	1,15	0,61

#### • Constant power (Power [W/cell], 25 [°C] / 77[°F])


F.V. V/cell	Discharge time										
	5 min	10min	15min	30min	1h	2h	3h	5h	8h	10h	20h
1,80	72,31	53,23	42,66	25,38	14,56	8,00	5,83	4,02	2,707	2,246	1,182
1,75	83,70	57,67	44,62	26,35	14,99	8,21	5,95	4,08	2,747	2,280	1,200
1,70	88,93	59,74	46,00	26,95	15,26	8,32	6,00	4,10	2,762	2,291	1,206
1,65	92,92	61,18	47,06	27,33	15,45	8,39	6,04	4,12	2,769	2,298	1,210
1,60	96,00	62,40	48,00	27,60	15,60	8,46	6,08	4,13	2,772	2,298	1,210

F.V. - Final voltage


## Battery life characteristics of standby use




## Battery life characteristics of cycle use




## Battery discharge characteristics




## Battery self discharge characteristics



## Battery charging characteristics for the standby use



## Battery charging characteristics for the cycle use



## Battery discharge current and final discharge voltage

Discharge current [A]	2.4 > I	2.4 ≤ I < 6.0	6.0 ≤ I < 12.0	12.0 ≤ I
Final discharge voltage [V/cell]	1.75	1.70	1.55	1.30



\*) C - Capacity