



Ups Evo DSP Plus 6.5 PF 0,9

Ups Evo DSP Plus 6.0-10.0 PF 0,9

POWER FACTOR **0,9**

- 1 RS232 port 2 USB port 3 Slot for SNMP interface, Dry Contact or MODBUS (for EVO DSP Plus 6.5 PF 0,9 in place of USB and RS232) 4 EPO connector  
5 Switch mains input 6 Input/output terminal block 7 Connector for external Battery Box 8 Manual bypass switch for maintenance

**Main Specifications**

- Local Area Network (LAN), Data Centers, Industrial equipment, Electromedical equipment
- Power factor 0,9
- Rectifier realized by IGBT technology
- Compatible with generators
- Battery charging system controlled by microprocessor
- Extension Back-up time by external Battery box (optional, only for EVO DSP PLUS MM 6.0-10.0 PF 0,9)
- Static and Manual Bypass (only for EVO DSP PLUS MM 6.0-10.0 PF 0,9)
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

HIGH EFFICIENCY  
**94%****Specifications**

UPS Model	EVO DSP PLUS 6.5 PF 0,9	EVO DSP PLUS 6.0 PF 0,9				EVO DSP PLUS 10.0 PF 0,9			
	FGCEVDP6503MM	FGCEVDP6MM2/00	FGCEVDP6MM2/C	FGCEVDP6MM2/D	FGCEVDP6MM2/E	FGCEVDP10MM2/00	FGCEVDP10MM2/C	FGCEVDP10MM2/D	FGCEVDP10MM2/E
Nominal power	6.5 KVA	6 KVA				10 KVA			
Active power	5.8 KW	5.4 KW				9 KW			
Power factor	0,9								
Technology	On-Line Double Conversion transformerless (VFI-SS-111)								
Cooling	Fan cooling								
Audible noise	< 48 dBA to 1 m	< 55 dBA to 1 m				< 58 dBA to 1 m			
Dimension (UPS) WxHxD	19x57,3x36,9 cm	19x68,8x36,9 cm				19x68,8x44,2 cm			
Dimension (with packing) WxHxD	33x83,5x50,5 cm	32x92,2x51,4 cm				32x92,2x58,7 cm			
Weight	46 Kg	18 Kg	57 Kg	62 Kg	65 Kg	23 Kg	62 Kg	67 Kg	70 Kg
<b>Input</b>									
Number of phases	1Ph+N								
Nominal voltage	208Vac/220Vac/230Vac/240Vac								
Input voltage range	176Vac-300Vac from 50% to the 100% of loading, 110Vac-300Vac up to 50% load								
Nominal frequency	50/60 Hz (selectable)								
Input frequency range (On-Line mode)	±7%								
Input power factor	0,99								
<b>Output</b>									
Number of phases	1Ph+N								
Nominal voltage	208Vac/220Vac/230Vac/240Vac								
Voltage Regulation at %100 linear load (On-Line and Battery mode)	±2%								
Voltage THD at rated linear load	<3% (linear load), <5% (non-linear load)								
Crest factor	3:1								
Frequency	50/60 Hz (selectable)								
Frequency stability	±0,1 Hz								
Inverter waveform	Sinewave								
Overload capability (Line mode)	110% for 30 minutes, 130% for 5 minutes, >130% for 10 seconds								
Overload capability (Battery mode)	110% for 3 minutes, 130% for 30 seconds, >130% for 10 seconds								
Efficiency	94%, calculated in double conversion mode at 100% load to 100% load according to standard 62040-3								
Transfer time	0 ms (On-Line)								
<b>Battery</b>									
Type	Lead acid, sealed, maintenance free								
Installed inside	12 elements	-	16 elements		-	16 elements			
Extended autonomy	External Battery Box (optional)								
<b>Environmental specification</b>									
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)								
Humidity	< 95% without condensation								
Maximum altitude	3000 m								
IP protection	IP20								
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)								

© 2020 Tecnoware Power Systems. The technical data may change without prior notice.

**Accessories**

Model	Code
Bypass Box for Evo Dsp Plus 6.0 and 10.0	FGCBYP10MM2
Dry Contact DB9 Interface	FGCEVODSDRY3
Dry Contact 9 PIN Interface	FGCEVODSDRY4

Model	Code
SNMP for Evo Dsp Plus MM	FGCNETAG7
ModBus RS485 Interface	FGCMODBUS





- ① Thermal Fuse protecting the battery charger circuit    ② Power Socket for the battery charger circuit    ③ Thermal switch for battery circuit  
 ④ Connector for the UPS connection    ⑤ Extra Battery Box connector

### Main Specifications

- Internal battery charger on every unit
- Units can be expanded infinitely
- Batteries with thermal circuit protection
- Easy connection to UPS
- Reduced dimensions
- Easy installation and maintenance

### Specifications

Model	BATTERY BOX FOR EVO DSP PLUS 6.0-10.0 PF 0,9													
Code	FBBEVDP192A/00	FBBEVDP192A/07	FBBEVDP192A/14	FBBEVDP192A/21	FBBEVDP192A/28	FBBEVDP192A/05	FBBEVDP192A/18	FBBEVDP192A/27	FBBEVDP192A/36	FBBEVDP192A/11	FBBEVDP192A/22	FBBEVDP192A/33	FBBEVDP192A/44	
Box dimension WxHxD	25 x 83,3 x 80 cm													
Pack dimension WxHxD	38 x 105,8 x 96,5 cm													
Weight	49 Kg	81,4 Kg	107,8 Kg	134,2 Kg	160,6 kg	90,5 kg	126 kg	161,5 Kg	197,1 Kg	98,2 Kg	141,4 Kg	184,6 Kg	227,8 Kg	
<b>Battery</b>														
Type	Lead acid, sealed, maintenance free													
<b>Internal battery charger</b>														
Nominal input voltage	230Vac													
Nominal input frequency	50/60Hz													
Nominal charging voltage	219,2Vdc													
Max charging current	Selectable	0,7A	1,4A	2,1A	2,8A	0,9A	1,8A	2,7A	3,6A	1,1A	2,2A	3,3A	4,4A	
<b>Protection</b>														
Battery charge input	Thermal fuse													
Battery circuit	Magnetothermic switch													
<b>Environmental specification</b>														
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)													
Humidity	< 95% without condensation													
Maximum altitude	3000 m													
IP protection	IP20													
Certifications	CE													

© 2020 Tecnoware Power Systems. The technical data may change without prior notice.