

230 Vac



1 On/Off switch 2 Led Line/Battery/Fault 3 Power cable 4 Input thermal protection 5 Output sockets with blackout protection 6 Filtered output socket 7 USB Port

Main Specifications

- Personal Computer, Modem/Router, Cash Register, Pos
- Automatic Voltage Regulation circuit (AVR)
- Output sockets for blackout protection
- Output sockets for overvoltage protection
- USB Port
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

Specifications

UPS Model	ERA PLUS STRIP 1.000	ERA PLUS STRIP 1.500	ERA PLUS STRIP 1.000 UK	ERA PLUS STRIP 1.500 UK
Code	FGCERAPLST1000	FGCERAPLST1500	FGCERAPLST1000UK	FGCERAPLST1500UK
Nominal power	1.000 VA	1.500 VA	1.000 VA	1.500 VA
Active power	700 W	1.050 W	700 W	1.050 W
Power factor	0,7			
Technology	Line Interactive with stabilizer			
Cooling	Natural			
Audible noise	< 40 dBA to 1 m			
Input connection	Fixed cable with Schuko plug		Fixed cable with UK plug	
Outlets	3 UPS outputs Schuko/Italian + 2 only filtered output Schuko/Italian		2 UPS outputs IEC + 2 UPS outputs UK + 2 only filtered output UK	
Dimension (UPS) WxHxD	20x9,1x29,2 cm			
Dimension (with packing) WxHxD	27x14x37,6 cm			
Weight	5,3 Kg	5,9 Kg	5,3 Kg	5,9 Kg
Input				
Number of phases	1Ph+N			
Nominal voltage	Single-phase 230Vac			
Input voltage range	+20%/-25%			
Nominal frequency	50/60 Hz (automatic selection)			
Input frequency range	+/-5%			
Output				
Number of phases	1Ph+N			
Nominal voltage	Single-phase 230Vac			
Voltage regulation (Line mode)	AVR (Automatic Voltage Regulation)			
Voltage regulation (Battery mode)	+/-5%			
Frequency	50/60 Hz (automatic selection)			
Inverter waveform	Modified sinewave			
Overload capability	< 130%			
Transfer time	2 ms (typical)			
Battery				
Type	Lead acid, sealed, maintenance free			
Backup time (typical)	10-70 min			
Environmental specification				
Working temperature	From 0 to 40 °C (retcomended from 20 to 25 °C)			
Humidity	< 95% without condensation			
Maximum altitude	3000 m			
IP protection	IP20			
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)			

© 2020 Tecnoware Power Systems. The technical data may change without prior notice.

Available on request with input/output nominal voltage 110Vac or 120Vac and with input plug and output sockets for specific country.