

LAN-Cable, Outdoor

Category 6

HELUKAT® 300A

U/UTP, outdoor



Cable structure


Inner conductor Ø:
Conductor material:
Core insulation:
Core colours:
Separator:
Screen over stranding element:
Screen 1 over stranding:
Screen 2 over stranding:
Outer sheath material:
Outer diameter:
Outer sheath colour:

U/UTP 4x2xAWG 24/ 1 PE

0,55 mm
Copper, bare
PE
whbu/bu, whog/og, whgn/gn, whbn/bn
Polyester foil over stranded bundle
-
-
PE
app. 6,4 mm
Black similar to RAL 9005

Electrical data

Characteristic impedance: 100 Ohm ± 15 Ohm at 1 to 100 MHz
100 Ohm ± 20 Ohm at 101 to 300 MHz
Loop resistance: 190 Ohm/km max.
Mutual capacitance: 50 nF/km nom.
Rel. propagation velocity: 67 %




Typical values

Frequency (MHz)	10	16	62,5	100	155	200	300
Attenuation (db/100m)	5,6	7,0	14,3	18,2	22,9	26,0	32,5
Next (db)	72,0	70,0	65,0	63,0	60,0	57,0	55,0
ACR (db)	66,4	63,0	50,7	44,8	37,1	31,0	22,5

Technical data

Weight: app. 47 kg/km
bending radius, repeated: 52 mm
Operating temperature range min.: -20°C
Operating temperature range max.: +60°C
Caloric load, approx. value: 0,30 MJ/m
Copper weight: 19,00 kg/km



Norms

Acc. to ISO/IEC 11801, Acc. to EN 50173, Acc. to EIA/TIA 568-A, Category 6, Halogen-free acc. to 60754-2

Application

HELUKAT® 300A outdoor data cables are used in the tertiary level of a network. They are characterized by large performance reserves and outstanding performance. They can be used to implement services such as Gigabit Ethernet, Fast Ethernet, Ethernet, ATM155, FDDI, token ring 4/16 Mbit/s, or ISDN absolutely trouble-free. Likewise, the mechanical characteristics are perfectly suited for the application in ducts or along buildings due to their optimized construction.

Part no.

805683, U/UTP 4x2xAWG24/1 PE (UTP)

Dimensions and specifications may be changed without prior notice.