



H3C MSR2600

Router Series

Branch Router

Release Date: February, 2021



Product overview

The MSR2600 router series can be deployed as an egress router for small- to medium-sized enterprise networks to operate with VPN, NAT, and IPSec service gateways. Together with other H3C products, the MSR2600 can provide comprehensive network solutions for government, power, financial, tax, public security, railway, and education customers.

The MSR2600 series has the following models: MSR2600-6-X1-GL.



H3C MSR2600-6-X1-GL router

Features and benefits

Advanced technologies

- Uses H3C's leading Comware network operating system to provide intelligent service scheduling management mechanism, and supports loose coupling of different service modules as well as the dynamic loading of processes and patches.
- Adopts an outstanding high-performance, multi-core CPU processor, which greatly enhances concurrent multi-service processing capabilities.
- Uses H3C-proprietary innovative intelligent link engine CUBE technology that not only enhances SIC card bus bandwidth, but also enables automatic interface resource allocation.

Powerful security features

- Service security
 - Packet filtering, including stateful filtering, MAC address filtering, IP and port number filtering, and time range filtering.
 - Real-time traffic analysis.
- Network security
 - Rich and comprehensive VPN technologies, including IPSec, L2TP, GRE, MPLS VPN and mix usage of different VPN technologies.
 - Routing security protection, including OSPF/RIP/IS-IS/BGP dynamic routing protocol, OSPFv3/RIPng/IS-ISv6/BGP IPSec encryption and rich routing policy control functions.
- End device access security
 - Unified endpoint access binding authentication, including EAD secure check authentication, 802.1X authentication, endpoint MAC address authentication, web-based portal authentication, endpoint access static binding, and MAC address auto-learning and binding.

- ARP attack prevention, including fixed source MAC address, ARP attack protection, ARP source suppression, ARP detection, source MAC consistency check and protection, ARP rate limit, and ARP active acknowledgement mechanism.
- Equipment management security
 - Role-based access control that allocates resources based on roles, and provides users and roles mapping.
 - Control plane traffic restriction, traffic control and filtering based on protocol type, queue, known protocol and specific protocol.
 - Remote security management, such as SNMPv3, SSH, and HTTPS remote management.
 - Management behavior control and audit, including AAA server central authentication, command line authority and real-time report of operation records.

Granular control

- Uses granular identification and control to rate limit and filter application layer services and ensure bandwidth and provides detailed network statistics for network optimization.
- Performs load balancing based on bandwidth, user, user group, service, or application by using asymmetric link, traffic load balancing, and multi-topology dynamic routing technologies.
- Supports flexible bandwidth sharing based on service, user, user group, link, and user bandwidth.

Intelligent network management

- Comprehensive network management methods—Supports command line and SNMP.
- Zero-configuration setup—Enables zero configuration setup and USB-based automatic configuration.
- Comware embedded EAA function—Monitors the internal events and status of the system's software and hardware components. If a fault occurs, it collects diagnostic information and attempts to make automatic repairs as well as sending the diagnostic information to a specific email address.

High availability

- Independent hardware processing module for monitoring and programmable components that supports online upgrade and auto loading to strengthen product reliability.
- Millisecond link fault detection technology Bidirectional Forwarding Detection (BFD) and Track between BFD and static routing, RIP/OSPF/BGP/ISIS dynamic routing, VRRP, or interface backup.
- Network quality analyzer (NQA) and Track between NQA and static routing, VRRP, or interface backup.
- Multi-device redundancy and load balancing (VRRP/VRRPE).
- Fast reroute, and GR/NSR.

Cloud interconnection

- Support of using VXLAN to provide Layer 2 connection in data centers. VXLAN-provided Layer 2 connection can be achieved simply by deploying edge devices with VXLAN capabilities without changing the original network structure. This reduces the networking cost and can provide enhanced security for traffic transmitted in the public network if used together with IPsec technologies.

Technical specifications

Hardware specifications

Item	MSR2600-6-X1-GL
CPU	1.6GHz
Forwarding Performance In Service (IMIX)	800 Mbps
Memory	1 G
Flash	256 MB
USB ports	1
CON ports	1
AUX ports	N/A
WAN ports	1 × GE copper port 1 × SFP port
LAN ports	4 × GE ports (can be configured as WAN interfaces)
SIC slots	2
DSIC slots	N/A
Maximum power consumption	30 W
Power input	100 to 240 VAC @ 50 Hz/60 Hz
Rack height	1 RU
Dimensions (H × W × D)	44.2 × 360 × 300 mm (1.74 × 14.17 × 11.81 in)
Weight	3.15 kg (6.94 lb)
Operating temperature	0°C to 45°C (32°F to 113°F)
Operating humidity	5% RH to 95% RH, non-condensing
EMC	FCC Part 15 (CFR 47) CLASS A
	ICES-003 CLASS A
	VCCI-3 CLASS A
	VCCI-4 CLASS A
	CISPR 22 CLASS A
	EN 55022 CLASS A
	AS/NZS CISPR22 CLASS A
	CISPR 24
	EN 55024
	EN 61000-3-2
	EN 61000-3-3
EN 61000-6-1	

Item	MSR2600-6-X1-GL
	ETSI EN 300 386
	EN 301 489-1
	EN 301 489-17
	UL 60950-1
	CAN/CSA C22.2 No 60950-1
	IEC 60950-1
	EN 60950-1/A11
Security	AS/NZS 60950
	EN 60825-1
	EN 60825-2
	FDA 21 CFR Subchapter J
	GB 4943

Software specifications

Item	Specification
Layer 2 switching	Ethernet, Ethernet II, VLAN (port-based VLAN, guest VLAN), 802.3x, 802.1p, 802.1Q, 802.1X, STP (802.1D), RSTP (802.1w), MSTP (802.1s), PPP, PPPoE client, PPPoE server, HDLC, and DDR
IP services	Unicast/multicast, TCP, UDP, IP option, IP unnumbered, policy-based routing, NetStream, and sFlow
IP application	Ping, Tracert, ICMP, DHCP server, DHCP relay, DHCP client, DNS client, DNS proxy, DDNS, NTP, and SNTP
IPv4 routing	Static routing
	Dynamic routing: RIPv1/v2, OSPFv2, BGP, IS-IS
	Route iteration
	Policy routing
IPv6	Equal-cost multi-path routing (ECMP)
	Multicast routing: IGMPv1/v2/v3, PIM-DM, PIM-SM, MBGP, MSDP
	IPv6 ND, IPv6 PMTU, IPv6 FIB, IPv6 ACL, NAT-PT, 6PE, and DS-LITE
	IPv6 tunneling: Manual tunneling, automatic tunneling, GRE tunnel, 6to4, ISATAP
QoS	Static routing
	Dynamic routing: RIPng, OSPFv3, IS-ISv6, BGP4+
	IPv6 multicast: MLDv1/v2, PIM-DM, PIM-SM
	LR, port-based mirroring, Port Trust Mode, and port priority
QoS	Committed access rate (CAR)
	FIFO, WFQ, CBQ



Item	Specification
	Generic Traffic Shaping (GTS)
	Traffic classification
3G/4G	Support for TDD/FDD LTE, TD-SCDMA, CDMA2000/EVDO, and WCDMA/HSPA+
	PPPoE client & server, portal, 802.1X
	Local authentication, RBAC, RADIUS, TACACS+
	Basic Firewall Function, ASPF, ACL, filter, connection limit
Security	IKE, IPsec
	L2TP, NAT/NAPT, PKI, RSA, SSH v1.5/2.0, URPF, mGRE, GRE
	ARP attack prevention
	SSL VPN, ADVPN, GDVPN
	AES, DES, 3DES, MD5, SHA1
	LDP, Static LSP
MPLS	L3VPN: Inter-AS MPS VPN (Option 1/2/3), MPLS nested VPN, hierarchy of PE (HoPE), dual-homed CE, MCE, and multirole host
	L2VPN: Martini, Kompella, CCC PWs and static PWs
	MPLS TE, RSVP TE
	VRRP, VRRPv3
High availability	Bandwidth-based load balancing and backup
	IP address-based load balancing and backup
	NQA collaboration with routing, VRRP or interface backup
	SNMP v1/v2c/v3, MIB, SYSLOG, RMON
Management and maintenance	BiMS remote management, booting from USB drive
	CLI, file system, and dual image
	DHCP, FTP, HTTP, ICMP, UDP public, UDP private, TCP public, TCP private, and SNMP
	Console port login, Telnet (VTY) login, SSH login, and FTP login

Ordering information

Model	Description
RT-MSR2600-6-X1-GL	H3C MSR2600-6-X1 Gigabit Router(2GE WAN,4GE LAN/WAN)
SIC module	
RT-SIC-4GSWF	4-port 100BASE-FX/1000BASE-X(SFP) Ethernet L2/L3 SIC Module
RT-SIC-4GSW	4-Port 10/100/1000BASE-T L2 Switch SIC Module



The Leader in Digital Solutions

New H3C Technologies Co., Limited

Beijing Headquarters

Tower 1, LSH Center, 8 Guangshun South Street, Chaoyang District, Beijing, China

Zip: 100102

Hangzhou Headquarters

No.466 Changhe Road, Binjiang District, Hangzhou, Zhejiang, China

Zip: 310052

Tel: +86-571-86760000

Copyright ©2021 New H3C Technologies Co., Limited Reserves all rights

Disclaimer: Though H3C strives to provide accurate information in this document, we cannot guarantee that details do not contain any technical error or printing error. Therefore, H3C cannot accept responsibility for any inaccuracy in this document. H3C reserves the right for the modification of the contents herein without prior notification

<http://www.h3c.com>