







Code	YGE12-130
Design Number	26302008E
Nominal Capacity (Ah)	130
Box Type / Number of Cells	D2H / 6
Voltage (V)	12
Electrolite Type	Gel
Weight (kg) (+ - %5)	43,4
Dimensions (mm) L / W / H (H1-H2)	345/174/263-286 [+5/-1mm]
Terminal Type	Round Type (DIN 72311-4) + M8 Optional
Float Voltage	13,6 - 13,8 VDC @25°C
Cycle Voltage	14,25 - 14,6 VDC @25°C
Recommended Charging Current Limit (Ah)	13
Discharge Cut-Off Voltage %100 Depth of Discharge D.O.D.	1,75 VDC @ (A) <=0,2 C
Capacity C20 (Ah)	130,0
Capacity C10 (Ah)	121,7
Capacity C5 (Ah)	111,8
Capacity C3 (Ah)	102,1
Self Discharge	Less than %2 per month @25°C
Storage Time	6 months @25°C. Charge Recommended Before Using
Cycle Life DOD %80	650
Cycle Life DOD %50	1200
Cycle Life DOD %20	3200




 **Terminal Type A**
DIN 72311-4 Round Type

Layout (0)



 **Terminal Type S**
(M-8 Optional)





Yiğit Akü A.Ş.

Organize Sanayi Bölgesi Oğuz Caddesi No: 2 Sincan / Ankara - TURKEY

Tel : +90 312 267 02 80 - Fax: +90 312 267 08 61 - 267 40 00

endustriyel@yigitaku.com

www.yigitaku.com