

DA100



GENERAL DESCRIPTION

Optima Drop Arm Turnstile provides aesthetic and effective control of entry or exit at kinds of toll collection systems like train/metro stations, and access control for commercial centers, stadiums, schools, government, and private sector buildings, etc.

SYSTEM SPECIFICATIONS

- ➔ Main body and lateral lids are AISI 304-grade stainless steel.
- ➔ Top cover tempered glass.
- ➔ Lateral covers are removable for easy maintenance.
- ➔ Motor start and stop control is maintained by Optima Control card.
- ➔ Low power consumption and silent running.
- ➔ Compatible with all access control systems.
- ➔ Turnstile is equipped with an alarm system which senses forbidden and reverse direction passing.
- ➔ Turnstiles closes flaps by itself after adjusted time if a valid card is presented but person not passed.
- ➔ All the obstacles in the passage are sensed with photoelectric sensors.
- ➔ Indoor use only.

ENVIRONMENTAL CONDITIONS AND POWER REQUIREMENT

- ➔ Between -15°C and +65°C, 95% non-condensing humidity; 220-240 VAC, mono phase, 50-60 Hz.
- ➔ Power Consumption 200 W (Max).

OPTIONAL ACCESSORIES

- ➔ Push button box.
- ➔ Card reader system.
- ➔ Digital Counter.
- ➔ Card reader mounting plate inside or on the turnstile.
- ➔ Card reader mounting plate with pedestal.
- ➔ Stainless steel railing.
- ➔ Uninterrupted power supply (UPS).
- ➔ SCADA or any control system: It is possible to change and check the position of turnstile with touch screen control panel, mobile devices (ios-android), computer, etc.

MAIN BODY MEASUREMENTS

