

# Product data sheet

Specifications



## APC Smart-UPS SRT 192V 8 and 10kVA RM Battery Pack



SRT192RMBP2

### Overview

Lead time Usually in Stock

### Main

Product or Component Type	External battery pack
Number of rack unit	3U
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide Warranty card Rack Mounting brackets
Range of Product	Smart-UPS Battery Systems

### Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Stand alone battery stack
Battery Voltage	+/- 192 V
RBC Quantity	2
Replacement battery	<a href="#">APCRBC140</a>

### Physical

Color	Black
Height	5.1 in (130 mm)
Width	17.008 in (432 mm)
Depth	26.9 in (682.7 mm)
Net Weight	200.6 lb(US) (91 kg)
Mounting Mode	Rack-mounted
Two post mountable	1

### Output

Battery Capacity 10 Ah

### Conformance

Standards OSHPD

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environmental

---

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0...15240 m)
Storage Relative Humidity	0...95 % non-condensing

## Ordering and shipping details

---

GTIN	731304292753
------	--------------

## Packing Units

---

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	16.5 in (42 cm)
Package 1 Width	23.6 in (60 cm)
Package 1 Length	39.4 in (100 cm)
Package weight(Lbs)	232.6 lb(US) (105.5 kg)

## Contractual warranty

---

Warranty (in months)	24
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint	483 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	390 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	26 kg CO2 eq.
Carbon footprint of the installation phase [A5]	30 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	368 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	37 kg CO2 eq.

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	488c31fb-3af8-42cf-9558-1362d000a07e
REACH Regulation	<a href="#">REACH Declaration</a>
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

### Use Longer

#### Lifetime extension

Repair	No
--------	----

### Use Again

#### Repack and remanufacture

Recyclability potential, in %	48
Circularity Profile	<a href="#">End of Life Information</a>
Removable battery	User replaceable
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

---

